

**特點**

- 採用大功率**晶元光電**燈珠,壽命可達30000~50000小時
- 本體為鋁合金材質,散熱性佳,性能穩定,啟動快,無頻閃,低光衰
- 搭配高性能恆流驅動電源,達到高效節能的目的
- 綠色環保,不含鉛、汞等有害物質,不會產生紫外光、紅外光等輻射
- 採用光學透鏡材質,透光率高

**Features**




- Using high power LED light sources, life span is up to 30,000-50,000Hrs
- Aluminum alloy, Good heat dissipation, stable performance, starting fast, no flickering
- With constant-current power supply, conversion efficiency is greater and energy saving
- No mercury pollution, no UV and IR radiation
- Using optical lens, high transmittance

**適用範圍**

產品可廣泛用於超市、商場、餐廳、飯店、展覽館、會議室及家庭等場所的照明裝飾

**Applications**

1. Residential lighting: indoor, decorative
2. Commercial building lighting: hotels, restaurants, factory, hospitals, museums, shops, super market...etc.



型號 Model No.	LED功率 LED Power (W)	系統功率 System Consumption (W)	光通量 Luminous Flux (Lm)	光角 Light Angle (°)	色溫 Color Temperature (K)	演色性 Color Rendering Index (Ra)	燈珠數量 Number of LEDs (pcs)	工作溫度 Operating Temperature (°C)	開孔孔徑 Cutting Hole (mm)	尺寸 Dimension (mm)
LED-240312300A	3W	5W	290Lm	30°	3000±200K(warm white)	85	3	-10 ~ +50°C	75mm	Ø85 x 30mm
LED-240612300A			315Lm		6000±200K(white)	80				Ø85 x 48mm
LED-240316300A	5W	7W	340Lm	45°	3000±200K(warm white)	85	5		95mm	Ø110 x 65mm
LED-240616300A			525Lm		6000±200K(white)	80				
LED-250316300A			340Lm		3000±200K(warm white)	85				
LED-250616300A			525Lm		6000±200K(white)	80				



**LED 崁燈驅動電源**  
**LED Power Supply**

Model No.: LD-81316300SM / LD-81324300

**LD-81316300SM**

- 輸入電壓 / Input voltage : AC100 -240V, 50/60Hz
- 輸出電壓 / Output voltage : 16VDC
- 輸出電流 / Output current : 300mA
- 尺寸 / Dimension : 59 x 20 x 19 mm( LxWxH)

**LD-81324300**

- 輸入電壓 / Input voltage : AC100 -240V, 50/60Hz
- 輸出電壓 / Output voltage : 24VDC
- 輸出電流 / Output current : 300mA
- 尺寸 / Dimension : 59 x 20 x 19 mm( LxWxH)